

FLEX RESINA 10-3000

Led Strip



Alimentazione / Operating Voltage	24 V
Potenza / Power	10 W/mt
Larghezza Pcb / Width Pcb	10 mm
Altezza / Height Stripe	2 mm
Lunghezza / Length Stripe	5000 mm
Taglio segmento/ Length per Cut	50 mm
N° LED	120 / mt
IP	20
Temperatura esercizio Storage Temperature	- 30° C - + 70°C
Lifetime	L70B20 50000H

	Flusso Luminoso Luminous Flux	Efficienza Efficiency	Colore Luce Led Color
DA-RESINA10-3000	697 lm/mt	70 lm/mt	3000 K



Via Cadorna, 40/42
20032 Cormano (MI)
Tel. +39 02 84269630
Fax +39 02 84269631
info@dadalighting.com
www.dadalighting.com



FLEX RESINA 10-3000

Led Strip

Light efficiency:

70 Lumen/Watt

Light quality:

CRI: 92,4

Color temperature:


3075 K

Output: 697 lm

Peak: 229 cd

Power: 10,0 W

24,0V @ 0,417A



Beam angle


116,2°

Color







CIE1931
x: 0,429
y: 0,396

Spectra



FLEX RESINA 10-3000

Led Strip



CRI R values, only R1-R8 are used to calculate final CRI value


R1	R2	R3	R4	R5	R6	R7	R8	R9	R10	R11	R12	R13	R14	R15
93,06	95,86	96,54	92,46	92,42	93,93	92,07	82,86	61,02	88,97	92,69	77,96	93,91	97,46	89,84

TM30 C values, 16 binned values out of total of 99 C values

C1	C2	C3	C4	C5	C6	C7	C8	C9	C10	C11	C12	C13	C14	C15	C16
90,91	91,49	87,30	92,61	92,55	93,86	92,94	96,49	93,86	87,39	85,24	89,12	92,41	87,85	89,33	85,47

CQS Q values

Q1	Q2	Q3	Q4	Q5	Q6	Q7	Q8	Q9	Q10	Q11	Q12	Q13	Q14	Q15
89,26	97,08	84,87	85,19	89,88	90,57	88,39	90,87	97,30	91,77	90,69	90,37	91,03	87,20	87,67




Color parameters

CCT	CRI	CRI R9	TM30 Rf	TM30 Rg	CQS	x	y	u	v	Duv
3075 K	92,4	61,0	90,5	100,8	89,5	0,4	0,4	0,2	0,3	-0,0023

FLEX RESINA 10-3000

Led Strip



Intensities in 0° c-plane

0°	5°	10°	15°	20°	25°	30°	35°	40°	45°	50°	55°	60°	65°	70°	75°	80°	85°	90°	95°
229	228	225	222	216	208	199	187	174	159	143	125	107	89	70	52	35	20	7	3
100%	100%	99%	97%	94%	91%	87%	82%	76%	70%	62%	55%	47%	39%	31%	23%	15%	9%	3%	1%

Intensities in 0° c-plane

0°	5°	10°	15°	20°	25°	30°	35°	40°	45°	50°	55°	60°	65°	70°	75°	80°	85°	90°	95°
229	228	225	222	216	208	199	187	174	159	143	125	107	89	70	52	35	20	7	3
100%	100%	99%	97%	94%	91%	87%	82%	76%	70%	62%	55%	47%	39%	31%	23%	15%	9%	3%	1%

Intensities in 180° c-plane

0°	5°	10°	15°	20°	25°	30°	35°	40°	45°	50°	55°	60°	65°	70°	75°	80°	85°	90°	95°
229	227	224	219	213	205	196	185	171	157	142	125	107	88	69	50	31	15	6	1
100%	99%	98%	96%	93%	90%	86%	81%	75%	69%	62%	55%	47%	39%	30%	22%	14%	7%	2%	0%

Intensities in 180° c-plane

0°	5°	10°	15°	20°	25°	30°	35°	40°	45°	50°	55°	60°	65°	70°	75°	80°	85°	90°	95°
229	227	224	219	213	205	196	185	171	157	142	125	107	88	69	50	31	15	6	1
100%	99%	98%	96%	93%	90%	86%	81%	75%	69%	62%	55%	47%	39%	30%	22%	14%	7%	2%	0%

Beam angle 50%	Field angle 10%	Cutoff angle 2,5%	Intensity ratio in 120° cone	Intensity ratio in 90° cone
116,2°	166,5°	180,7°	76,0%	51,2%